



12687 Last Updated: 5/27/2004 Resin Number:

Material Number: Page 1 of 1

DESCRIPTION

Durez 12687 is a finely pulverized two-step phenolic resin.

APPLICATION

Durez 12687 is recommended for use as a processing aid and reinforcing resin for NBR (nitrile) rubber and adhesives.

FEATURES

Durez 12687 provides hardness and heat resistance. It has a medium cure and a rigid set.

TYPICAL PROPERTIES

		Test Method
Appearance	Brown powder	DCT 0001
Melt Point Clear, °C	75.00	DCT 0011B
% Hexa	7.40	DCT 0126B
Cure @ 165°C, sec	27.00	DCT 0162B
Specific Gravity	1.18	DCT 0170
IPF @ 125°C, mm (0.5g)	75.00	DCT 0351C
Screen % on 200 Mesh	1.0	DCT 4007A

Durez test methods are available upon request.

STORAGE

This product is a stable material that has little or no tendency to lump when maintained in closed containers. Store in a cool, dry location at 75°F or less.

PACKAGING AND SHIPPING

Available in non-returnable fiber drums, 200 pounds net. This product is not DOT regulated in drums.

READ THE MATERIAL SAFETY DATA SHEET BEFORE HANDLING, STORING OR USING THIS PRODUCT.



use remains the responsibility of the customer. No suddestions for use are intended as and nothing herein shall be

construed as a recomendation to infringe any existing patents or to violate any Federal, State or local laws.